

Specs. On a Recycling Trailer

30 Yard Aluminum Trailer with hard Top

All Aluminum box

Total length not to exceed 24'6" from tongue to rear

Low profile loading height of 48" – 50"

5 sliding doors each side

Sliding side loading doors adjust to 5 loading positions; load from either side; gap sealed with brush type seal

Door handles spring loaded stainless steel

Variable compartment sizes

Interior height minimum of 68" from floor to roof

Dual gas props on the top half of the compartment

2 point tailgate assembly operates from street side

Blue box hooks

Trailer frame constructed from heavy duty 8 in channel Color Black

Tandem axel, with trailer brakes

Twin 6000 lb torsion axels

Heavy gauge steel fenders

1 Adjustable bulk head

A heavy adjustable Lunette eye on the A- Frame tongue with a 7000 lb drop leg jack stand

2 fabricated steps, 1 on each side of the front of the trailer

O — ring or JIC hydraulic fittings

2 wire type, 4000 psi pressure housing

Push button operation with key safety switch

45 degree dump angle

6" x 21" double acting hoist cylinder

Up to 30,000lb hoist capacity

1 spare tire

Recessed lights in system with flashing amber beacon light

Automatic reset circuit breakers

Protective cable or conduit wiring

Standard light package to meet federal DOT standards (LED LIGHTS)

Any Questions call 315-271-5290

Jamie Bechy